

Declare. SM

Omega 400 Series Thermally Broken Omega Windows and Doors

Final Assembly: Multiple Locations in New Zealand

Life Expectancy: 15-25 Year(s)

End of Life Options: Recyclable (Aluminium and Glass 95%),
Landfill (5% remaining ingredients)

Ingredients:

Unnamed Material: Aluminum; Float glass; Zinc; Iron;
Poly[imino(1,6-dioxo-1,6- hexanediyl)imino-1,6-hexanediyl];
Sulfide polymer (Na₂); Zinc oxide; Synthetic calcium carbonate;
Stainless steel; Carbon black; Paraffin; Tin chloride (SnCl₂);
Calcined Kaolin; Ethyl Acetate; Hydrogen Fluoride; Titanium
dioxide; 1,2-Benzenedicarboxylic acid, 4-sulfo-; 1,2,3-
Trihydroxybenzene; 5-Sulphosalicylic acid dihydrate;
Magnesium; Sulfamic acid; Sulfuric acid, tin(2++) salt (1:1);
Acetone; Argon; Methyl Ethyl Ketone; Naphtha (petroleum),
hydrodesulfurized heavy; Toluene

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

OMG-0001

EXP. 01 MAY 2025

Original Issue Date: 2020